



INSTALLATION INSTRUCTIONS

Part Number: VF3006

This filter fits: SEE CATALOG FOR CURRENT APPLICATIONS

* FREE K&N® decal To register your warranty, please see us online at knfilters.com/register. FREE K&N® decal *

K&N® Cabin Air Filters replace your vehicle's stock cabin filter with a reusable design that cleans and freshens incoming air. They are electrostatically charged to grab and hold dust particles. K&N® cabin air filters help control odors while they help capture most mold, mildew, fungus, spores, bacteria and germs. When they get dirty they can be cleaned and reused and best of all, they come with a 10 year/Million mile limited warranty.

If you need any assistance please call 1-800-858-3333 to speak with a representative in our Customer Service Center before returning the product.

When applicable, refer to owner's manual for manufacturers installation/removal instructions. The following are helpful steps when replacing/servicing cabin air filter with K&N® cabin air filter.

1. Open glove box compartment and remove the two screws by the glove box striker and the two screws behind the cap covers. Fig. 1&2
2. Locate fuse box cover and remove cover to expose the two screws. Remove screws. Fig. 3&4
3. Remove panel between the radio and center console to expose one screw. Remove screw. Fig. 5
4. After all screws are taken off, you will be able to remove the lower dash panel.
5. Locate the four screws holding the glove box and remove them. Fig. 6
6. Carefully pull out the glove box enough to expose the pigtail located on the left side. You must unclip this pigtail in order to remove the glove box entirely from the dashboard. Fig. 7
7. Remove two screws holding the crossbar. **NOTE: Do not remove the bolt holding the ground wire. Let the cross bar hang freely, but make sure it is not pulling the ground wire.** Fig. 8&9
8. Locate cabin filter housing and remove cover. Fig. 10
9. Pull both cabin filter trays out of housing.
10. Remove dirty cabin filters out of trays. Remove any debris that might be present on the cabin filter trays or inside housing. Fig. 11
11. Install K&N® Cabin Filter. Once filter is installed correctly the filter will sit flush. Fig. 12
12. Reverse steps 1-10 to complete cabin filter installation. With the cabin filter installed, clean an area on the housing and apply the K&N® Stop Decal. The decal will help notify others that this is a reusable cabin filter.



Fig. 1



Fig. 2



Fig. 3



Fig. 4



Fig. 5



Fig. 6



Fig. 7



Fig. 8



Fig. 9



Fig. 10



Fig. 11



Fig. 12

Please visit our website knfilters.com for a complete listing of other K&N® products for your vehicle, such as oil filters, air filters, and intake kits. We recommend refreshing your K&N® Cabin Air Filter every 12 months, or 12,000 miles. Use K&N® Refresher kit pt.# 99-6000 which includes the easy to follow instructions.