



INSTALLATION INSTRUCTIONS

Part Number YA-1201

This filter fits: SEE CATALOG FOR CURRENT APPLICATIONS

Congratulations, you have purchased the finest air filter that money can buy. With proper care, this filter can last many seasons. This filter can be used in a stock machine, with no modifications required. If any engine modifications have been made tuning/jetting adjustments may be required. There are special installation instructions, so please follow the procedures outlined below to ensure the K&N Filtercharger® seals properly.

INSTALLATION

1. Remove the stock air filter and air filter tray.
2. Remove the stock air filter from the air filter tray.
3. Clean the sealing surfaces where the tray contacts the air box and where the air filter contacts the tray.
4. Service the air filter tray gasket according to the owners manual.
5. Apply a thin layer of the provided K&N Sealing Grease to the base of the K&N Filtercharger®.
6. Install the K&N Filtercharger® onto the stock air filter tray and tighten the wing nut.
7. Install the stock air filter tray and the K&N Filtercharger® into the air box. (Fig. 1)
Note: Once positioned in air box, the “up” arrow on the K&N Filtercharger® will need to be in a vertical position.
8. Reinstall the air box cover.

THESE INSTRUCTIONS MUST BE FOLLOWED EVERY TIME THE FILTER IS SERVICED, OTHERWISE THE FILTER MAY NOT SEAL, AND DAMAGE TO THE ENGINE COULD RESULT.



Fig. 1